WO 2005/041619 PCT/US2004/014907

9

CLAIMS

005732-000033.CB.280512

10

15

20

30

5 1. A microwave cooking device comprising:

at least one first container defining at least one first volume for holding a food product, the container including at least one venting mechanism; and

a second container operatively coupled to the at least one first container, wherein the second container defines a second volume, the second container including at least one venting mechanism;

wherein steam created by the cooking of the food product in the at least one first container creates a first pressure treatment for the food product before venting into the second volume defined by the second container, wherein the second volume creates a second pressure treatment for the food product as a result of steam venting from the first container into the second container.

- 2. The device of claim 1, wherein the at least one first container is a first receptacle.
- 3. The device of claim 2, wherein the second container is a second receptacle.
- 4. The device of claim 2, the first receptacle further including a peripheral edge.
- 5. The device of claim 4, wherein the at least one first volume is defined by sealing a cover to the peripheral edge of the first receptacle.
 - 6. The device of claim 2, wherein the second container encloses the first receptacle.
 - 7. The device of claim 3, wherein the second receptacle encloses the first container.

WO 2005/041619 PCT/US2004/014907

10

- 8. The device of claim 1, wherein the at least one first container is a cup having an opening.
- 9. The device of claim 8, wherein the at least one first volume is defined by the5 cup and a cover sealed over the opening.
 - 10. The device of claim 9, wherein the second container is an additional cover sealed over the opening of the cup.
- 10 11. The device of claim 1, wherein the second container is a box.
 - 12. The device of claim 1, wherein the second container encloses the at least one first container.
- 13. The device of claim 1, wherein the at least one first container is a lower sealed portion of a cooking bag.
 - 14. The device of claim 1, wherein the second container is a cooking bag.
- 20 15. The device of claim 1, having a plurality of first containers.
 - 16. The device of claim 15, wherein the second container encloses all of the first containers.
- 25 17. The device of claim 1, wherein the at least one first container defines a plurality of separate volumes.
 - 18. The device of claim 17, wherein the at least one first container is enclosed within the second container.
 - 19. The device of claim 1, further including an insulating container.

30

WO 2005/041619 PCT/US2004/014907

11

20. A method for improving microwave cooking comprising:

providing a first container defining a first volume for holding food including at least one venting mechanism for enabling steam to exit the container;

5

providing a second container defining a second volume including at least one venting mechanism for enabling steam to exit the container; and arranging the first container and the second container to allow steam that escapes the first volume to enter the second volume.